



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON B Resin
Code-Nr. 100501

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 3	H412	

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

Signal word

Warning

Hazard Statements

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

- P102 Keep out of reach of children.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing.
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

1,6-hexanediol, reaction products with chloromethyloxirane, bis-[4-(2,3-epoxypropoxy)phenyl]propane, bisphenol f epoxy resin

! Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
9003-36-5	500-006-8	bisphenol f epoxy resin	2,5 < 10	Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed 05.08.2019
revision 02.11.2018 (GB) Version 9.0

WEICON B Resin

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	5 < 10	Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411 M=0
933999-84-9	618-939-5	1,6-hexanediol, reaction products with chloromethyloxirane	2,5 < 10	Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412 M=0

REACH

CAS No	Name	REACH registration number
9003-36-5	bisphenol f epoxy resin	01-2119454392-40
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	01-2119456619-26
933999-84-9	1,6-hexanediol, reaction products with chloromethyloxirane	01-2119463471-41

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

Give water to drink in small sips.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

vomiting

Nausea

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

Metal oxides

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)



5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 02.11.2018 (GB) Version 9.0

WEICON B Resin

Advice on storage compatibility

Do not store with acids or alkalis.
Do not store together with animal feedstuffs.
Do not store together with food.
Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed, store at cool and aired place, open and handle carefully.
Protect from heat and direct solar radiation.
Storage temperature between 2°C to 40°C

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL-/PNEC-values

DNEL worker

CAS No	Substance name	Value	Code	Remark
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl] propane	8,33 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
		12,25 mg/m ³	DNEL acute inhalative (systemic)	
		12,25 mg/m ³	DNEL long-term inhalative (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
9003-36-5	bisphenol f epoxy resin	0,0083 mg/cm ²	DNEL acute dermal, short-term (local)	
		104,15 mg/kg	DNEL long-term dermal (systemic)	
		29,39 mg/m ³	DNEL long-term inhalative (systemic)	
933999-84-9	1,6-hexanediol, reaction products with chloromethyloxirane	0,0226 mg/cm ²	DNEL acute dermal, short-term (local)	
		10,57 mg/m ³	DNEL acute inhalative (systemic)	
		0,44 mg/m ³	DNEL long-term inhalative (local)	
		0,0226 mg/cm ²	DNEL long-term dermal (local)	
		10,57 mg/m ³	DNEL long-term inhalative (systemic)	
6 mg/kg	DNEL long-term dermal (systemic)			

PNEC

CAS No	Substance name	Value	Code	Remark
9003-36-5	bisphenol f epoxy resin	0,294 mg/kg	PNEC sediment, freshwater	
		0,0006 mg/l	PNEC aquatic, marine water	
		11 mg/kg	PNEC Secondary Poisoning	
		10 mg/l	PNEC sewage treatment plant (STP)	
933999-84-9	1,6-hexanediol, reaction products with chloromethyloxirane	1 mg/l	PNEC sewage treatment plant (STP)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 9.0

WEICON B Resin

DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		0,001 mg/l	PNEC aquatic, marine water	
		0,283 mg/kg	PNEC sediment, freshwater	
		0,028 mg/kg	PNEC sediment, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short term: filter apparatus, filter AX

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: FKM, NBR (Nitrile rubber), >=8 h, 0,35 - 0,4 mm

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

pasty

Colour

black

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	ca. 7	25 °C			500 g/l
boiling point	not determined				
melting point	not determined				
Flash point	> 200 °C			DIN 51758	Pensky-Martens Closed Cup
Vapourisation rate	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 9.0

WEICON B Resin

	Value	Temperature	at	Method	Remark
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 0,2 Pa	20 °C			
Relative density	3,28 g/cm ³	25 °C			
Vapour density	not determined				
Solubility in water		20 °C			more or less insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	190 - 200 Pa*s	50 °C			
Viscosity kinematic	not determined				
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids.

Reactions with oxidising agents.

Reactions with alkalis.

**10.4. Conditions to avoid**

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Alkali (lye), concentrated

Acid, concentrated

Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Halogenated hydrocarbons

Toxic gases/vapours

Thermal decomposition

Remark No decomposition below 200°C.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg	rat	OECD 420	CAS: 1675-54-3
LD50 acute dermal	> 2000 mg/kg	rat		CAS: 1675-54-3
Skin irritation	irritant	rabbit	OECD 404	
Eye irritation	irritant	rabbit eye	OECD 405	
Skin sensitization	sensitizing		OECD 429	

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity	NOAEL 50 mg/kg (90 d) Repeated Dose 90-Day Oral Toxicity Study in Rodents OECD 408			-
Mutagenicity	OECD 478			No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity	NOEL 540 mg/kg Experimental value CAS: 1675-54-3	Rat	OECD 416	No indications of toxic effects were observed in reproduction studies in animals.

**WEICON B Resin**

Value	Species	Method	Validation
Carcinogenicity		OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	No indications of carcinogenic effects are available from long-term trials.
Carcinogenicity Studies / 7d/week / 2 years CAS: 1675-54-3			

Experiences made from practice

Sensitization through skin contact possible.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 1,5 mg/l (96 h)	Oncorhynchus mykiss	OECD 203	CAS: 1675-54-3
Daphnia	EC50 2,55 mg/l (48 h)	Daphnia magna	Conversion value	CAS: 9003-36-5
Algae	EC50 1,8 mg/l (72 h)	Green algae	OECD 201	CAS: 9003-36-5
Bacteria	IC50 > 100 mg/l (3 h)	activated sludge		CAS: 1675-54-3

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	5 % (28 d) CAS: 1675-54-3		OECD 301 F	not readily degradable
Degradability	47 % (28 d) CAS: 933999-84-9		OECD 301 D	not degradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.11.2018 (GB) Version 9.0

WEICON B Resin

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Listed in: EINECS (EEC) ; TSCA (USA); DSL (Ca)

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.1

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.