

# AL-T High Performance Grease



**high temperature grease**  
**long-term lubrication**

WEICON AL-T high performance grease is a universally usable high temperature grease for long-term lubrication. WEICON AL-T is suitable for rolling and sliding bearings, joints, levers, sliding guides, spindles, spline shafts and at all sliding speeds permitted for grease lubrication.

## Technical Data

Abbreviation (DIN 51502)	KPL 2 R -20
Consistency assignment (DIN 51818)	NLGI-Class 2
Base	Aluminium complex soap / mineral oil
Colour	darkbrown
Density at +20°C (+68°F) (DIN 51757)	0,94 g/cm <sup>3</sup>
VKA-TEST (DIN 51350) welding load	2.400 N
VKA-TEST (DIN 51350) goods load	2.200 N
VKA-TEST (DIN 51350) Spherical cap value (1Min/1000N)	2,0 mm
Speed identifying value	400.000
Worked penetration (DIN ISO 2137)	265 - 295 1/10 mm
Water resistance (DIN 51807)	0 - 90
Specific heat transfer capacity (20°C)	1,490 J/(g·K)
Thermal diffusivity (20°C)	0,265 mm <sup>2</sup> /s
Thermal conductivity (ISO 22007-4) (20°C)	0,372 W/m·K
Dielectric strength (DIN EN 60243-1) (20°C)	11,0 kV/mm
Drop Point (IP 396)	> 210 °C
Kinematic viscosity (DIN 51562) at +40°C	230 mm <sup>2</sup> /s
Kinematic viscosity (DIN 51562) at +100°C	16 mm <sup>2</sup> /s
EMCOR corrosion test (DIN 51 802)	0 / 0
Storage stability	24 months
Temperature resistance	-25 to +190 °C
IMPA-Code	450444/45

## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

## Surface pre-treatment

Clean surfaces.

## Processing

Apply AL-T evenly.

## Storage

Keep in closed original container. Do not store together with oxidizing agents. Keep container tightly closed and store at cool and ventilated place. Recommended storage temperature: room temperature.

## Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

## Available sizes:

26600040	AL-T High Performance Grease 400 g
26600100	AL-T High Performance Grease 1.0 kg
26600500	AL-T High Performance Grease 5.0 kg
26600925	AL-T High Performance Grease 25.0 kg

## Accessories:

10953001	Processing Spatula, short
10953003	Processing Spatula, long

WEICON GmbH & Co. KG  
(Headquarters)  
Germany  
phone +49 (0) 251 9322 0  
info@weicon.de  
www.weicon.de

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae  
www.weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca  
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Turkey  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr  
www.weicon.com.tr

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com  
www.weicon.com.ro

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za  
www.weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
phone (+65) 6710 7671  
info@weicon.com.sg  
www.weicon.com.sg

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz  
www.weicon.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es  
www.weicon.es

WEICON Italia S.r.l.  
Italy  
phone (+39) 0102924871  
info@weicon.it  
www.weicon.it