### **ΨΕΙ<u></u>ΟΠ**

High-Performance Greases

## Silicone Grease HV



## Special lubricant for valves, fittings and seals | drinking water approval | NSF registration | BAM

WEICON Silicone Grease HV is strong, transparent and shows very good compatibility to plastics. Due to its NSF H1 registration, WEICON Silicone Grease is suitable as lubricant in sensitive areas where inadvertent contact to food is possible. Complies with the Guideline for Hygienic Assessment of Organic Materials in Contact with Drinking Water (KTW Guideline) by the Federal Environment Agency. It can be used in the food and beverage industry, in sanitary and heating construction, in the pharmaceutical industry as well as in the sealing technology. WEICON Silicone Grease HV is BAM safety-tested - see leaflet 034-1 "List of non-metallic materials for use in oxygen" (DGUV information 213-075) of BG RCI. The grease is particularly material-friendly, neutral in odour and taste and has a temperature resistance of -50°C to +200°C.

WEICON Silicone Grease HV is suitable for the lubrication of plastics, rubber parts and seals, valves, fittings and gaskets, machines, equipment, slow rotating bearings and as assembly aid for O-rings.

Technical Data		
Consistency classification	DIN 51818	NLGI grade 3
Base		Dimethylpolysiloxane
Colour		colourless
Density	(+20 °C)	>1,00 g/ml
Dielectric strength	DIN EN 60243-1 (20°C)	9,2 kV/mm
Dripping point	IP 396	> +200 °C
Flashpoint		> +300°C
EMCOR-corrosion test	DIN 51 802	1/2
Temperature resistance		-40°C to +200°C
Shelf life		24 mon.

# Lubricating and Multifunctional Oils

#### Approvals / Guidelines

NSF Hygiene Institute

H1 (FDA 21 CFR) Risk group P2

#### Surface pre-treatment

Clean surfaces.

#### Processing

Apply Silicone Grease evenly.

#### Shelf life

Store in tightly closed original container. Do not store with oxidising agents. Keep container tightly closed and store in a cool, well-ventilated area. Recommended storage temperature:. Room temperature.

#### Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

#### **Available sizes**

26300045Silicone Grease HV, 450 g, colourless26300100Silicone Grease HV, 1 kg, colourless26300500Silicone Grease HV, 5 kg, colourless26300925Silicone Grease HV, 25 kg, colourless

#### **Conversion table**

$(^{\circ}C \times 1,8) + 32 = ^{\circ}F$ mm/25,4 = inch µm/25,4 = mil N x 0,225 = lb N/mm <sup>2</sup> x 145 = psi	Nm x 8,851 = $lb \cdot in$ Nm x 0,738 = $lb \cdot ft$ Nm x 141,62 = $oz \cdot in$ mPa $\cdot s = cP$ N/cm x 0,571 = $lb/in$
MPa x 145 = psi	$kV/mm \times 25,4 = V/mil$

To the product detail



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarante the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es WEICON GmbH & Co. KG (Headquaters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Italia S.r.L. Italy phone +39 (0) 010 2924 871 info@weicon.it WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr